Ø30 Round Push Button Switches (S3PR Series)

Time	Appearance		Contact block		LED block		
Туре		Model	A contact	B contact	AC/DC voltage	AC voltage	
Extended		S3PR-P1□A(M)	1	_			
		S3PR-P1 □2A(M)	2	_			
	S3PR-P1R□	S3PR-P1□3A(M)	3	3 —			
		S3PR-P1□B(M)	_	1	_	_	
		S3PR-P1 □2B(M)	_	2			
		S3PR-P1 □3B(M)	_	_ 3			
		S3PR-P1□AB(M)	1	1			
		S3PR-P1□2AB(M)	2	1			
		S3PR-P1□A2B(M)	1	2			
		 ※□ indicates color: R, B, G, Y, K ※The M in the model name indicates modular type contact block. Models without M are singular contact block. ※The control unit, contact blocks, LED blocks are sold separately. (control unit: bold letters, contact block: regular letters) • Dimensions 					
			Panel t	hickness: Max. 6mm		(unit: mm)	
		8 B Singular type 50.5 27.0 Modular type 48.5 25.0					
			**For panel cut-out dimensions, please refer to page A			er to page A-105	
Гуре	Appearance	Model	Contact block		LED block	A 0 . II	
-, ,		00DE D4[[4 (44)	A contact	B contact	AC/DC voltage	AC voltage	
lush		S3PF-P1 A(M)	1	_	_		
		S3PF-P1 2A(M)	2	_	_		
		S3PF-P1□3A(M)	3	_	_		
		S3PF-P1□B(M)	-	2	_		
		S3PF-P1 □2B(M) S3PF-P1 □3B(M)	_	3		_	
		S3PF-P1□AB(M)	1	1	-		
		S3PF-P1□2AB(M)	2	1	-		
		S3PF-P1 □A2B(M)	1	2			
	S3PF-P1B□	 ※□ indicates color: , , , , , , , , , , , , , , , , , , ,					
		• Dimensions	Panel thic	kness: Max. 6mm	<u></u>	(unit: mm)	

Ø36

3.2

B 27.0

Singular type 57.6

Modular type 55.6

XFor panel cut-out dimensions, please refer to page A-105.

A-84 Autonics

48.1

30.4

			Contact block	Contact block		LED block	
ype Appearance		Model	A contact	B contact	AC/DC voltage	AC voltage	
ush		S3PF(U)-P3□ADM	1	_	3	Ao voltage	
uminated)		S3PF(U)-P3 □2ADM	2				
		S3PF(U)-P3□BDM		1	1	_	
	act	S3PF(U)-P3□2BDM	_	2			
	Modular contact	S3PF(U)-P3 ABDM	1	1			
	ar c	. ,	1			1	
	l in	S3PF(U)-P3 ALM	•	-	_		
	M	S3PF(U)-P3 2ALM	2	_			
		S3PF(U)-P3 BLM		1			
		S3PF(U)-P3 □2BLM		2			
		S3PF(U)-P3 ABLM	1	1			
S3PFU	XT (c XC XM m XT	 ※□ indicates color: N. D. N. W. ※The control unit, contact blocks, LED blocks are sold separately. (control unit: bold letters, contact block: regular letters) ※Control unit+contact block (modular type) models do not contain "Push" markings on the button cap. ※Models with 'U' in the model name is available only for control unit. 'U' models do not contain "Push" markings on the button cap. ※The LED color is the same as the control unit. ※Waterproof cap (model: SA-WP) is available. Dimensions 					
		monoro	Danal thickness	o: Mov. 6mm		(unit: mm)	
			Panel thickness	o. IVIGA. UITIITI			
	188.1						
	\ \ <u>\</u>			25			
		30.4	3.4 57.8	-			
					ensions, please refe	er to page A-10	
Appearance		Model	Contact block		LED block		
			A contact	B contact	AC/DC voltage	AC voltage	
		S3PF(U)-P3 □AD	1				
		S3PF(U)-P3□2AD	2	_			
	t	S3PF(U)-P3 □BD		1	1	-	
	Singular contact	S3PF(U)-P3 □2BD		2			
	8	S3PF(U)-P3□ABD	1	1			
		S3PF(U)-P3□AL	1	-			
	 	S3PF(U)-P3□2AL	2	_			
		S3PF(U)-P3□BL		1		1	
		S3PF(U)-P3 □2BL		2			
		S3PF(U)-P3□ABL	1	1			
S3PF	×T (c ×C ×M m	indicates color: [,],	ss, LED blocks are act block: regular le ngular type) models ame is available of	etters) s contain "Push" nly for control un	markings on the but it. 'U' models do not up (model: SA-WP) i	contain "Push"	
		mensions		Myrater proof cap (I			
			Panel th	Panel thickness: Max. 6mm		(unit: mm)	
		46.1	960		38.4		

Autonics A-85

%For panel cut-out dimensions, please refer to page A-105.

Ø30 Panel Cut-out Dimensions

Ø30 Panel Cut-out Dimensions

(unit: mm)

Туре	A	В	Panel Cut-out Dimensions	
Round Push Button Switches (S3PR/S3PF Series)		45	55	Ar., A+0.5
Round Selector Switches	Short lever	37	55	Min. A ^{±0.5} Ø30.5
(S3SF/S3SFN Series)	Long lever	55	55	Min.B ^{±0.5}
Round Key Selector Switch (S3KF Series)	37	55		
Pilot Lights (L3RF Series)		37	55	

Push Button Switches Round Square

Ø16

Ø22/25

□30

Selector Switches Round Square

Key Selector Switches Round Square

Rectangular

Double Push Button Switches

Mushroom-head Push Button Switches

Emergency Switches

Pilot Lights

Accessories

Buzzers

Autonics A-105